

TECHNICAL DATA SHEET				
PRODUCT CODE	DHM630A		REF NO: TDV/F04/04	
PRODUCT NAME	DOUBLE SIDE COATED 630 GSM FOOD GRADE		DEF: 18/02/2016	
APPROVALS	As per US FDA 21 CFR 175.300			
PARAMETER		TEST METHOD	UNIT	SPECIFICATION
COATING TYPE				PVC
PROPERTIES				WP, UV , PHTHALATE & LEAD FREE
FABRIC CONTENT				POLYESTER HIGH TENACITY
WEIGHT		IS 1964	GSM	630
THICKNESS		IS 7702	MM	0.50
BREAKING STRENGTH	WARP	IS 1969 (P1)	KG/5CM	230 MIN
	WEFT			220 MIN
TEARING STRENGTH	WARP	IS 7016 (P3)	KG	35 MIN
	WEFT			30 MIN
ADHESION		IS 7016 (P5)	KG/5CM	7 MIN
WATER PROOFNESS @220 PSI		IS 7016 (P7)	MM	NO LEAK
PHTHALATE ESTERS		CPSC-CH-C1001-09.3	Mg/KG	NOT DETECTED
LEAD CONTENT		IS.12074	PPM	NOT DETECTED

Head Office & Work

Nobletex Industries Ltd.,
 Block No.309, N.H. - 8 Baleshwar-
 Palsana, Surat-394317 (Gujarat),
 India.

Registered Office :

Nobletex Industries Ltd.,
 301, Acme Plaza, Andheri Kurla Road,
 Andheri (E), Mumbai-400059 (Maharashtra)
 India.

Sqft Rtae: 21.00

CIN No. : U99999MH1985PLC118016